



(TOLERANCE±0.5mm)

P(NO )	L1	L2	P(NO )	L1	L2	P(NO )	L1	L2
1	6.5		11	56.5	50.0	21	106.5	100.0
2	11.5	5.0	12	61.5	55.0	22	111.5	105.0
3	16.5	10.0	13	66.5	60.0	23	116.5	110.0
4	21.5	15.0	14	71.5	65.0	24	121.5	115.0
5	26.5	20.0	15	76.5	70.0	25	126.5	120.0
6	31.5	25.0	16	81.5	75.0	26	131.5	125.0
7	36.5	30.0	17	86.5	80.0	27	136.5	130.0
8	41.5	35.5	18	91.5	85.0	28	141.5	135.0
9	46.5	40.0	19	96.5	90.0	29	146.5	140.0
10	51.5	45.0	20	101.5	95.0	30	151.5	145.0



**LIH SHENG PRECISION INDUSTRIAL CO., LTD.**

5	Knob	NORYL PPO SE1		UL94V-1
4	Cover	NYLON PA66 FR15		UL94V-0
3	Break Terminal	BRASS(C2680R-H)	Sn/cu 4~6	
2	Ring Spring	SUS 301		
1	Housing	NYLON PA66 FR15		UL94V-0
No	PART NAME	MATERIAL	PLATED	COLOR

TOLERANCE X ±0.5 X.X ±0.3 X.XX ±0.15	Material		PART NAME	Terminal Blocks	
	Thickness		PART NO.	LS-0623	
	Disposal		DATE	2006.03.24	REV: A
UNIT mm	SCALE	2:1	DRAW	CHECK	APPROVE
			Chris	Ken	Cooper